

> nationenan References

000000000

DEPUTY N

100003402

Distriction

Long and the second

ACOUSTIC AND THERMAL CONTROL OF STEAM TRAPS



SONAPHONE K

User-friendly Quick response time Reliable Cost-effective



SONAPHONE K

Acoustic and Thermal Control of Steam Traps and Valves



Ultrasonic probe

Battery charger

Headphone

noises

Temperature sensor

Integrated speaker

On/Off, Charge/Laden,

Temperature mode

<u>-10 ℃ up to</u> + 50 ℃

Temperature sensor Sound proofed headphone

Transportation case

Extension cable for the temperature

0 °C up to + 40 °C

SONAPHONE K

Ultrasonic probe

Leather bag

Instructions

sensor (1,5 m)

Charger

0 up to 800 ℃

Accuracy 2% Display on LCD By plastic foil keyboard

Ca. 10 hours

LED-Bar graph in 10 steps

Value on LCD similar to dB

Sound proofed headphones

Strong suppression of environmental

Technical Data

Optical display of the ultra-

Temperature measurement

Acoustical reproduction

Connectors

sonic intensity

Handling

optional

Operating time

Further displays

Operating temperature

Storage temperature

Scope of delivery

Application

- Exact detection of steam losses and defective steam traps
- Ultrasonic level measurement as an indicator for steam losses
- Integrated temperature measurement (condensate/steam)
- User-friendly, easy and quick operation by simply putting the probe on the measuring point

Operation

Function control of steam traps by controlling the sound level in the fitting. Defective drains differ in level very legibly from intact drains. Ultrasonic waves arising from defective steam traps are registered. The intensity of these ultrasonic waves are shown on a digital display. The integrated temperature measurement is a valuable support in order to asses either extremely high or extremely low temperatures.

Advantages

- Easy and reliable method
- Quick temperature measurement
- The reliable indication increases your plant safety and prevents condensate losses.



SONAPHONE K in the transportation case

SONOTEC Ultraschallsensorik Halle GmbH Nauendorfer Straße 2 D-06112 Halle (Saale) Tel. ++49 / (0)345 / 1 33 17-0 Fax ++49 / (0)345 / 1 33 17-99



www.sonotec.de e-mail: SONOTEC@sonotec.de